



CFS..MA 类型

预包装润滑脂

螺柱直径 (mm)	h6公差	类型代号		尺寸(mm)									基本额定动负荷 Cr N	基本额定静负荷 Cor N	最大允许载荷 N	最大拧紧力矩 N·m	质量 g (大约)	
		圆筒外圈	带保持架	满装滚子	D	C	d	G	G1	B1	B2	C1						H
2.5	0 -0.006	CFS 2.5MA	—	5	3	2.5	M2.5×0.45	2.5	9.5	5	0.7	0.9	4.8	370	300	260	0.2	1
		—	CFS 2.5VMA	920	990	260												
3	0 -0.006	CFS 3MA	—	6	4	3	M3×0.5	3	11.5	6	0.7	1.5	5.8	570	560	360	0.3	2
		—	CFS 3VMA	1 260	1 620	360												
4	0 -0.008	CFS 4MA	—	8	5	4	M4×0.7	4	15	8	1	2	7.7	990	990	780	0.6	4
		—	CFS 4VMA	2 160	2 790	780												
5	0 -0.008	CFS 5MA	—	10	6	5	M5×0.8	5	18	10	1	2.5	9.6	1 440	1 710	1 420	1.3	7
		—	CFS 5VMA	2 880	4 330	1 420												
6	0 -0.008	CFS 6MA	—	12	7	6	M6×1	6	21.5	12	1.2	3	11.6	1 890	1 980	2 110	2.3	13
		—	CFS 6VMA	4 240	5 760	2 110												

外圈公差 (μm)

类型	圆筒外圈
CFS2.5M, CFS3M, CFS4M, CFS5M, CFS6M	0/-8

附件

类型	附件
所有类型	不锈钢螺母 已预装