





# ROLLER FOLLOWERS

# STAINLESS STEEL



Type and Part Code

Type	Applicable axis diameter	Feature	Part Code
 <p>RNAST..M (Separable type)</p>	φ 7 ~ φ 60	Stainless type NAST..M type without inner ring.	<p><u>RNAST</u>   <u>15</u>   <u>M</u>   <u>R</u></p> <p>↑   ↑   ↑   ↑</p> <p>Type   Bore diameter</p> <p><b>Stainless steel</b>   <b>R</b>: Crowned outer ring <b>None</b>: Cylindrical outer ring</p>
 <p>NAST..M (Separable type)</p>	φ 6 ~ φ 50	Stainless type Thick walled outer ring, inner ring. Separable bearing with combined needle roller with precision cage.	<p><u>NAST</u>   <u>15</u>   <u>M</u>   <u>R</u></p> <p>↑   ↑   ↑   ↑</p> <p>Type   Bore diameter</p> <p><b>Stainless steel</b>   <b>R</b>: Crowned outer ring <b>None</b>: Cylindrical outer ring</p>
 <p>NAST..MZZ (Separable type)</p>	φ 6 ~ φ 50	Stainless type Separable bearing in which labyrinth seal is formed with combined side plate at both sides of inner ring of NAST type. (NAST..MZZUU type comes with seals)	<p><u>NAST</u>   <u>15</u>   <u>M</u>   <u>ZZ</u>   <u>UU</u>   <u>R</u></p> <p>↑   ↑   ↑   ↑   ↑   ↑</p> <p>Type   Bore diameter</p> <p><b>Stainless steel</b>   <b>ZZ</b>: With shield   <b>UU</b>: With seals</p> <p><b>R</b>: Crowned outer ring <b>X</b>: Cylindrical outer ring</p>
 <p>NART..MR (Non-separable type)</p>	φ 5 ~ φ 50	Stainless type Non-separable bearing with fixed side plate at inner ring. Mitigate eccentric load with spherical shape at outer diameter of outer ring (code R). (NART..MUUR type comes with seals)	<p><u>NART</u>   <u>15</u>   <u>M</u>   <u>UU</u>   <u>V</u>   <u>R</u></p> <p>↑   ↑   ↑   ↑   ↑   ↑</p> <p>Type   Bore diameter</p> <p><b>Stainless steel</b>   <b>UU</b>: Sealed type   <b>V</b>: Full complement <b>None</b>: Shield type   <b>None</b>: With cage</p> <p><b>R</b>: Crowned outer ring <b>X</b>: Cylindrical outer ring</p>