


滚子从动件


分离型 无内圈



RNAS T



RNAS T



RNAS T.R

RNAS T 类型

预包装润滑脂

轴直径 (mm)	类型代号		尺寸 (mm)				基本额定动负荷 	基本额定静负荷 	轨道载荷能力		允许转速 *	质量		
	圆筒外圈 	球面外圈 (R500) 											轨道载荷能力	
													F _w	D
7	RNAS T 5	RNAS T 5R	7 ^{+0.022} / _{+0.013}	16	7.8		0.3	2 740	2 390	2 350	1 080	30 000	8.9	
10	RNAS T 6	RNAS T 6R	10 ^{+0.027} / _{+0.016}	19	9.8		0.3	4 120	4 550	3 530	1 370	20 000	13.9	
12	RNAS T 8	RNAS T 8R	12 ^{+0.027} / _{+0.016}	24	9.8		0.6	5 680	5 890	4 020	1 860	17 000	23.5	
14	RNAS T10	RNAS T10R	14 ^{+0.027} / _{+0.016}	30	11.8		1	9 700	9 670	5 590	2 450	15 000	42.5	
16	RNAS T12	RNAS T12R	16 ^{+0.027} / _{+0.016}	32	11.8		1	10 400	10 900	5 980	2 740	13 000	49.5	
20	RNAS T15	RNAS T15R	20 ^{+0.033} / _{+0.020}	35	11.8		1	12 300	14 300	6 570	3 140	10 000	50	
22	RNAS T17	RNAS T17R	22 ^{+0.033} / _{+0.020}	40	15.8		1	17 400	20 900	10 900	3 720	9 500	90	
25	RNAS T20	RNAS T20R	25 ^{+0.033} / _{+0.020}	47	15.8		1	19 200	24 500	12 700	4 610	8 500	135	
30	RNAS T25	RNAS T25R	30 ^{+0.033} / _{+0.020}	52	15.8		1	20 700	28 400	14 100	5 290	7 000	152	
38	RNAS T30	RNAS T30R	38 ^{+0.041} / _{+0.025}	62	19.8		1	30 300	45 400	22 100	6 660	5 500	255	
42	RNAS T35	RNAS T35R	42 ^{+0.041} / _{+0.025}	72	19.8		1	32 200	50 600	25 700	8 130	5 000	375	
50	RNAS T40	RNAS T40R	50 ^{+0.041} / _{+0.025}	80	19.8		1.5	35 700	61 100	26 900	9 310	4 000	420	
55	RNAS T45	RNAS T45R	55 ^{+0.049} / _{+0.030}	85	19.8		1.5	37 100	66 400	28 500	10 100	4 000	460	
60	RNAS T50	RNAS T50R	60 ^{+0.049} / _{+0.030}	90	19.8		1.5	38 700	71 800	30 200	11 000	3 500	500	

* 适合润滑脂润滑。如果是油润滑，最大容许值可到该数值的 130%。

外圈公差 (μm)

类型	圆筒外圈	球面外圈
RNAS T5	0/-8	0/-50
RNAS T6,RNAS T8,RNAS T10	0/-9	0/-50
RNAS T12,RNAS T15,RNAS T17,RNAS T20	0/-11	0/-50
RNAS T25,RNAS T30,RNAS T35,RNAS T40	0/-13	0/-50
RNAS T45,RNAS T50	0/-15	0/-50